

In-Finity 70 Suspension Up & Down Emergency 3000K Micro-Prismatic Diffuser Dali

■ **N70UEM3U14BDA - Black**

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

Main specifications

Lamp category	LED	Environment	Indoor
Power (W)	35.9W/m		
CCT (K)	3000K		
CRI	80		
Mountings	Suspension		

Optical

Lighting type	Indirect, Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	72

Electrical


Dimmable	Yes
Driver	Integrated
Emergency	Without
Insulation class	I

Physical

Color	Black
Orientation	Fixed
Length (mm)	1400

Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



In-Finity 70 Suspension Up & Down Emergency 3000K Micro-Prismatic Diffuser Dali



5



5

Metal cover. Suspension Up & Down.
70 mm (Colour Anodized Grey)
08.9057.02

500 mm micro-prismatic diffuser.
Highly efficient multilayer diffuser
that, thanks to its unique
microprismatic texture, provides a
glare free UGR<19 light beam
08.0113.00

Metal cover. Suspension Up & Down.
70 mm
08.9057.06



5



5

Metal cover. Suspension Up & Down.
70 mm (Colour Black)
08.9057.NS

Power supply rose. Dali
08.0031.00.DA

Metal cover. Suspension Up & Down.
70 mm (Colour White)
08.9057.40



Suspension kit
08.0030