



130  
69  
73



## In-Finity 70 Suspension Up & Down Emergency 3000K Micro-Prismatic Diffuser

### ■ N70UEM3U02B - Anodized Grey

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

#### Main specifications

|                      |            |                    |                     |
|----------------------|------------|--------------------|---------------------|
| <b>Lamp category</b> | LED        | <b>Environment</b> | Indoor dry location |
| <b>Power (W)</b>     | 35.9W/m    |                    |                     |
| <b>CCT (K)</b>       | 3000K      |                    |                     |
| <b>CRI</b>           | 80         |                    |                     |
| <b>Mountings</b>     | Suspension |                    |                     |

#### Optical

|                           |                  |
|---------------------------|------------------|
| <b>Lighting type</b>      | Indirect, Direct |
| <b>LED type</b>           | Top LED          |
| <b>Light distribution</b> | Symmetric        |
| <b>Optical type</b>       | Diffused light   |
| <b>Beam angle (°)</b>     | 72               |

#### Electrical

|                         |              |
|-------------------------|--------------|
| <b>Dimmable</b>         | No           |
| <b>Driver</b>           | Integrated   |
| <b>Driver type</b>      | Non Dimmable |
| <b>Emergency</b>        | Without      |
| <b>Insulation class</b> | I            |

#### Physical

|                    |               |
|--------------------|---------------|
| <b>Color</b>       | Anodized Grey |
| <b>Orientation</b> | Fixed         |
| <b>Length (mm)</b> | 1400          |

#### Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 70 Suspension Up & Down Emergency 3000K Micro-Prismatic Diffuser



500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room  
08.0110.00



Metal cover. Suspension Up & Down.  
70 mm (Colour Anodized Grey)  
08.9057.02



Metal cover. Suspension Up & Down.  
70 mm (Colour White)  
08.9057.40



Power supply rose  
08.0031.00



Suspension kit  
08.0030



Metal cover. Suspension Up & Down.  
70 mm  
08.9057.06



Metal cover. Suspension Up & Down.  
70 mm (Colour Black)  
08.9057.NS