









In-Finity 70 Suspension Up & Down Emergency 4000K Micro-Prismatic Diffuser Dali

■ N70UEM4U14BDA - Black

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

Main specifications			
Lamp category Power (W) CCT (K) CRI Mountings	LED 35.9W/m 4000K 80 Suspension	Environment	Indoor dry location
Optical			
Lighting type LED type Light distribution Optical type Beam angle (°)	Indirect, Direct Top LED Symmetric Diffused light 72		
Electrical			
Dimmable Driver Driver type	Yes Integrated Dimmable DALI 1		
Emergency Insulation class	Without I		
Physical			
Color Orientation Length (mm)	Black Fixed 1400		

Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 70 Suspension Up & Down Emergency 4000K Micro-Prismatic Diffuser Dali



500 mm micro-prismatic diffuser. Highly efficient multilayer diffuser that, thanks to its unique microprismatic texture, provides a glare free UGR<19 light beam

08.0113.00



Suspension kit 08.0030



Metal cover. Suspension Up & Down. 70 mm (Colour Anodized Grey) 08.9057.02



Metal cover. Suspension Up & Down. 70 mm (Colour White) 08.9057.40



Metal cover. Suspension Up & Down. 70 mm 08.9057.06



Metal cover. Suspension Up & Down. 70 mm (Colour Black) 08.9057.NS



Power supply rose. Dali 08.0031.00.DA