

## In-Finity 70 Suspension Up & Down Emergency 4000K Micro-Prismatic Diffuser

■ **N70UEM4U02B - Anodized Grey**

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

### Main specifications

<b>Lamp category</b>	LED	<b>Environment</b>	Indoor dry location
<b>Power (W)</b>	35.9W/m		
<b>CCT (K)</b>	4000K		
<b>CRI</b>	80		
<b>Mountings</b>	Suspension		

### Optical

<b>Lighting type</b>	Indirect, Direct
<b>LED type</b>	Top LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Diffused light
<b>Beam angle (°)</b>	72

### Electrical


<b>Dimmable</b>	No
<b>Driver</b>	Integrated
<b>Driver type</b>	Non Dimmable
<b>Emergency</b>	Without
<b>Insulation class</b>	I

### Physical

<b>Color</b>	Anodized Grey
<b>Orientation</b>	Fixed
<b>Length (mm)</b>	1400

### Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



IP  
20

# In-Finity 70 Suspension Up & Down Emergency 4000K Micro-Prismatic Diffuser



500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room  
08.0110.00



Metal cover. Suspension Up & Down.  
70 mm (Colour Anodized Grey)  
08.9057.02



Metal cover. Suspension Up & Down.  
70 mm  
08.9057.06



Power supply rose  
08.0031.00



Metal cover. Suspension Up & Down.  
70 mm (Colour Black)  
08.9057.NS



Metal cover. Suspension Up & Down.  
70 mm (Colour White)  
08.9057.40



Suspension kit  
08.0030