



In-Finity 70 Suspension Up & Down Flat Corner 3000K General Lighting Dali

N70UFC3G02BDA - Anodized Grey


 ${\sf LED\ modular\ system\ for\ suspended\ installation, including\ LED\ luminaires, aluminum\ installation\ profile, and aluminum\ installation\ profile\ profi$ diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

Main specifications

Number of heads	1	Net lumen (lm)	3821
Lamp category	LED	Mountings	Suspension
Power (W)	35.9W/m	Environment	Indoor dry location
CCT (K)	3000K		
CRI	80		

Optical

Lighting type Indirect, Direct LED type Top LED Light distribution Symmetric Optical type Diffused light Beam angle (°) 102 Beam angle C90-270 (°) 106



Insulation class

<u>h(</u>m) E(lx)D(m) 957 2.45 2 239 4.90 3 106 7.34 4 60 9.79 5 38 12.24

Beam Angle DIR: 102°

_		
-	lectrica	
_	IECHICA.	

Frequency (Hz)	50/60
Dimmable	Yes
Driver	Integrated
Driver type	Dimmable DALI

Emergency Without

Physical

Color	Anodized Grey
Orientation	Fixed
Weight (kg)	4.10

Note

 $Opal\ Diffuser:\ Diffuse,\ glare\ free\ and\ uniform\ lighting\ throughout\ the\ room.\ /\ Emergency:\ Emergency\ Module$ available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 70 Suspension Up & Down Flat Corner 3000K General Lighting Dali





500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room 08.0110.00

Suspension kit 08.0030

Metal cover. Suspension Up & Down. 70 mm (Colour Anodized Grey) 08.9057.02



70 mm (Colour White)

08.9057.40

Metal cover. Suspension Up & Down. Power supply rose. Dali 08.0031.00.DA



Metal cover. Suspension Up & Down. 70 mm 08.9057.06



Metal cover. Suspension Up & Down. 70 mm (Colour Black) 08.9057.NS