

In-Finity 70 Suspension Up & Down Flat Corner 3000K General Lighting

N70UFC3G14B - Black

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.



Main specifications

Number of heads	1	**Net lumen (lm)**	3821
Lamp category	LED	**Mountings**	Suspension
Power (W)	35.9W/m	**Environment**	Indoor dry location
CCT (K)	3000K		
CRI	80		

Optical

Lighting type	Indirect, Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	102
Beam angle C90-270 (°)	106



Luminous flux luminaire
3821 lm

Beam Angle DIR: 102°

h(m)	E(lx)	D(m)
1	957	2.45
2	239	4.90
3	106	7.34
4	60	9.79
5	38	12.24

Electrical

Frequency (Hz)	50/60	**Insulation class**	I
Dimmable	No		
Driver	Integrated		
Driver type	Non Dimmable		
Emergency	Without		

Physical

Color	Black
Orientation	Fixed
Weight (kg)	4.10

Note

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-FInity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 70 Suspension Up & Down Flat Corner 3000K General Lighting

500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room
08.0110.00

Metal cover. Suspension Up & Down. 70 mm (Colour Anodized Grey)
08.9057.02

Metal cover. Suspension Up & Down. 70 mm (Colour White)
08.9057.40

Suspension kit
08.0030

Metal cover. Suspension Up & Down. 70 mm
08.9057.06

Metal cover. Suspension Up & Down. 70 mm (Colour Black)
08.9057.NS

Power supply rose
08.0031.00