



In-Finity 70 Suspension Up & Down Flat Corner 4000K General Lighting Dali

N70UFC4G30BDA - White

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.

Main specifications

Number of heads	1	Net lumen (lm)	4137
Lamp category	LED	Mountings	Suspension
Power (W)	35.9W/m	Environment	Indoor dry location
CCT (K)	4000K		
CRI	80		

Optical

Electrical Frequency (Hz)

Dimmable

Driver type Emergency

Physical

Orientation


Weight (kg)

Driver

Lighting type LED type Light distribution Optical type Beam angle (°) Beam angle C90-270 (°) Indirect, Direct Top LED Symmetric Diffused light 102 106

Fixed

4.10



Beam Angle DIR: 102°					
h(m)	E(İ x)	D(m)			
1	1036	2.45			
2	259	4.90			
3	115	7.34			
4	65	9.79			
5	41 <i>°</i>	12.24			

Luminous flux luminaire 4137 lm	

<u> </u>	1030	2.43
2	259	4.90
3	115	7.34
4	65	9.79
5	41	12.24

50/60 Insulation class Yes Integrated Dimmable DALI Without White

Note

Color

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Flnity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

In-Finity 70 Suspension Up & Down Flat Corner 4000K General Lighting Dali



Metal cover. Suspension Up & Down. 70 mm (Colour Anodized Grey) 08.9057.02

5

5

Metal cover. Suspension Up & Down. 70 mm (Colour White) 08.9057.40

Metal cover. Suspension Up & Down. 70 mm 08.9057.06

5



Metal cover. Suspension Up & Down. 70 mm (Colour Black) 08.9057.NS