

In-Finity 70 Suspension Up & Down Flat Corner 4000K Micro-Prismatic Diffuser

■ N70UFC4U14B - Black

LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.




Main specifications

Number of heads	1	Net lumen (lm)	3039
Lamp category	LED	Mountings	Suspension
Power (W)	35.9W/m	Environment	Indoor
CCT (K)	4000K		
CRI	80		

Optical


Lighting type	Indirect, Direct
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	67
Beam angle C90-270 (°)	76



Beam Angle DIR: 67°

h(m)	E(lx)	D(m)
1	1062	1.33
2	265	2.66
3	118	3.99
4	66	5.32
5	42	6.65

Luminous flux luminaire
3039 lm



Electrical


Frequency (Hz)	50/60	Insulation class	I
Dimmable	No		
Driver	Integrated		
Driver type	Electronic		
Emergency	Without		

Physical

Color	Black
Orientation	Fixed
Weight (kg)	4.10

Note

Micro-Prismatic Diffuser: Highly efficient multilayer diffuser that, thanks to its unique micro-prismatic texture, provides a glare free UGR<19 light beam. / Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.



In-Finity 70 Suspension Up & Down Flat Corner 4000K Micro-Prismatic Diffuser



5

Metal cover. Suspension Up & Down.
70 mm (Colour Anodized Grey)
08.9057.02



5

Metal cover. Suspension Up & Down.
70 mm
08.9057.06



Power supply rose
08.0031.00



5

Metal cover. Suspension Up & Down.
70 mm (Colour Black)
08.9057.NS



5

Metal cover. Suspension Up & Down.
70 mm (Colour White)
08.9057.40



Suspension kit
08.0030



500 mm opal diffuser. Diffuse, glare free and uniform lighting throughout the room
08.0110.00