

Indirect Light Tube 1200 mm

New

03.8411.14 - Black



Diffused indirect LED light module to be installed in the Infra-Structure Episode 2. Safety fixing and locking mechanical elements integrated for a transversal installation between two rods of the profile. The Light Tubes are only fed by one of the ends and do not communicate current through the other end. Each lighting element is completed...

Diffused indirect LED light module to be installed in the Infra-Structure Episode 2. Safety fixing and locking mechanical elements integrated for a transversal installation between two rods of the profile.

The Light Tubes are only fed by one of the ends and do not communicate current through the other end. Each lighting element is completed by a long 4m electrical cable equipped with an output microconnector.




Main specifications

Number of heads	1	Net lumen (lm)	1612
Lamp category	LED	Mountings	Ceiling surface
Power (W)	25.5W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	90		

Optical



Lighting type	Indirect
LED type	Top LED
Light distribution	Symmetric
Optical type	Diffused light
Beam angle ind (°)	99
Beam angle ind C90-270 (°)	93



Beam Angle: 93°

h(m)	E(lx)	D(m)
1	690	2.12
2	173	4.25
3	77	6.37
4	43	8.50
5	28	10.62

Luminous flux luminaire
1612 lm



Electrical

Dimmable	Yes
Driver	Remote excluded
Emergency	Without
Insulation class	III

Physical

Color	Black
Orientation	Fixed
Length (mm)	1200

Indirect Light Tube 1200 mm



LED Power Supply Source for remote installation. 48V/320W. 100/240 Vac
60.8919



Casambi Controller 220-240V. Remote Installation
60.9392



LED power supply source for remote installation, 48V/120W. 220/240 Vac
60.9170



LED Power Supply Source for remote installation. 48V. 100Vac (150W)-240Vac (200W)
60.9607



0/1-10V / DALI / PUSH Broadcast
60.9391