




Johnny 120 Light Source

03.0741.40 - White

Recessed luminaire with LED light source. Power supply not included. One driver is needed per each light source.




Main specifications

Number of heads	1	Net lumen (lm)	1324
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	18W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	90		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	13
Beam angle C90-270 (°)	13



Beam Angle:	13°		
	h(m)	E(lx)	D(m)
1	12785	0.22	
2	3196	0.44	
3	1421	0.66	
4	799	0.88	
5	511	1.10	

Luminous flux luminaire
1324 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	36.00	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Non Dimmable, Dimmable DALI 2, Dimmable Casambi, Dimmable 1-10V, Dimmable DALI 1, Mains Cut Dimming		

Physical

Color	White
Orientation	Adjustable
Recessed depth (mm)	160
Weight (kg)	0.50
Tilt (°)	40

Note

Unique reference for Trim or No Trim recessed installation. 08.0555.00=includes white frame to complete Trim finishing. 08.0505.00=includes optional white and black frames to complete Trim finishing.

Johnny 120 Light Source



Snoot shielding cone
08.0526.BW

Flood lens
08.8432.00


Snoot shielding cone
08.0526.00



Continuous current power supply of 10-20W, 110/240V – 50/60Hz with power current selected through adjustable 250 mA – 10W / 350 mA – 15W / 400 mA – 17W / 450 mA – 19W / 500/550/600/700 mA – 20W, Dali 1 switch.
60.8847

Continuous current power supply of 18W, 220/240V – 50/60Hz with 450 mA supply voltage Mains dimming, trailing edge
60.9268

Honeycomb
08.8428.00



Continuous current power supply of 13-20W, 110/240V – 50/60Hz with power

Continuous current power supply 220/240V – 50/60Hz. Adjustable Current

Elliptical lens
08.8431.00

400/450/500/550/600/
650/700/750/800/850/900 mA – 15W.
switch. 0/1-10V or push dimming
60.9188



24W / 600mA-27W / 650mA-29W /
700mA-31W / 750mA-32W / 800mA-33W
/ 850mA-35W / 900mA-38W / 950mA-
40W / 1000/1050mA-42W
60.9162



Snoot shielding cone
08.0526.40

Continuous current power supply.
230/240V – 50/60Hz. Adjustable Current
350mA – 17W / 500mA – 24W / 700/ 750
mA – 32W switch by trailing and
leading edge dimming, mains dimming
or push dimming
60.8534