

## Johnny 120 Semi-Recessed 1L Square – Housing

■ 08.0506.14 - Black

Recessed luminaire with LED light source. Power supply not included. One driver is needed per each light source.



### Main specifications


Mountings	Ceiling recessed
Environment	Indoor

### Electrical


Emergency	Without
Insulation class	III

### Physical


Color	Black
Weight (kg)	0.30



### Certification / Marking



# Johnny 120 Semi-Recessed 1L Square – Housing



Honeycomb  
08.8428.00

Flood lens  
08.8432.00

Elliptical lens  
08.8431.00



Snoot shielding cone  
08.0526.00

Screening crosspiece  
08.8429.00

Continuous current power supply of  
13-20W, 110\*/240V – 50/60Hz with  
power current selected through  
adjustable switch. Synchronisation  
cables not included.  
60.9188



Constant Current Power Supply for  
LED. Dimmable DALI. 10-20W  
60.8847

Continuous current power supply of  
12-20W, 110\*/240V – 50/60Hz with  
power current selected through  
adjustable switch. Synchronisation  
cables not included.  
60.9188

Continuous current power supply,  
Mains dimming 220/240V – 50/60Hz, 12-  
20W  
60.9188



---

Continuous current power supply,  
dimmable Casambi, 220/240V –  
50/60Hz, 35W – 650mA / 36W – 700 mA.  
60.9207

---

Non dimmable continuous current  
power supply of 220/240V – 50/60Hz  
with power current selected through  
adjustable with switch 200mA – 8,5W /  
250mA – 11W / 300mA – 13W / 350mA –  
15W / 400mA – 17,5W / 450mA 19,5W /  
500mA – 22W.  
60.9160