

Johnny 120 Semi-Recessed 2L Square – Housing

■ 08.0507.40 - White

Recessed luminaire with LED light source. Power supply not included. One driver is needed per each light source.



Main specifications



Mountings	Ceiling recessed
Environment	Indoor dry location

Electrical


Emergency	Without
Insulation class	III

Physical

Color	White
Weight (kg)	0.30



Johnny 120 Semi-Recessed 2L Square – Housing



Continuous current power supply of
13-20W, 110/240V – 50/60Hz with power
current selected through adjustable
300 mA – 15W / 350 mA – 18W /
400/450/500/550/600/
650/700/750/800/850/900 mA – 15W.
switch. 0/1-10V or push dimming
60.9188

Elliptical lens
08.8431.00


Continuous current power supply.
230/240V – 50/60Hz. Adjustable Current
350mA – 17W / 500mA – 24W / 700/ 750
mA – 32W switch by trailing and
leading edge dimming, mains dimming
or push dimming
60.8534



Flood lens
08.8432.00

Continuous current power supply of
10-20W, 110/240V – 50/60Hz with power
current selected through adjustable
250 mA – 10W / 350 mA – 15W /400 mA
– 17W /450 mA – 19W /500/550/600/700
mA – 20W, Dali 1 switch.
60.8847

Honeycomb
08.8428.00



Snoot shielding cone
08.0526.00

Continuous current power supply of
18W, 220/240V – 50/60Hz with 450 mA
supply voltage Mains dimming, trailing
edge
60.9268

Snoot shielding cone
08.0526.BW



Continuous current power supply
220/240V – 50/60Hz. Adjustable Current
300mA-13W / 350mA-15W / 400mA-18W
/ 450mA-20W / 500mA-22W / 550mA-
24W / 600mA-27W / 650mA-29W /
700mA-31W / 750mA-32W / 800mA-33W
/ 850mA-35W / 900mA-38W / 950mA-
40W / 1000/1050mA-42W
60.9162

Snoot shielding cone
08.0526.40