

Johnny 120 Semi-Recessed 2L Square – Housing

■ 08.0557.40 - White

Recessed luminaire with LED light source. Power supply not included. One driver is needed per each light source.



Main specifications



Mountings	Ceiling recessed
Environment	Indoor dry location

Electrical

Emergency	Without
Insulation class	III

Physical

Color	White
Weight (kg)	0.30



Johnny 120 Semi-Recessed 2L Square – Housing



Flood lens
08.8432.00

Snoot shielding cone
08.0526.40


Honeycomb
08.8428.00



Snoot shielding cone
08.0526.00

Continuous current power supply of 13-20W, 110/240V – 50/60Hz with power current selected through adjustable 300 mA – 15W / 350 mA – 18W / 400/450/500/550/600/ 650/700/750/800/850/900 mA – 15W. switch. 0/1-10V or push dimming
60.9188

Continuous current power supply of 10-20W, 110/240V – 50/60Hz with power current selected through adjustable 250 mA – 10W / 350 mA – 15W / 400 mA – 17W / 450 mA – 19W / 500/550/600/700 mA – 20W, Dali 1 switch.
60.8847



Snoot shielding cone

Continuous current power supply.

Elliptical lens

mA – 32W switch by trailing and leading edge dimming, mains dimming or push dimming
60.8534



Continuous current power supply of 18W, 220/240V – 50/60Hz with 450 mA supply voltage Mains dimming, trailing edge
60.9268

Continuous current power supply 220/240V – 50/60Hz. Adjustable Current 300mA-13W / 350mA-15W / 400mA-18W / 450mA-20W / 500mA-22W / 550mA-24W / 600mA-27W / 650mA-29W / 700mA-31W / 750mA-32W / 800mA-33W / 850mA-35W / 900mA-38W / 950mA-40W / 1000/1050mA-42W
60.9162