

Johnny 120 Square 1L – Recessed Universal Frame

■ 08.0550.00 - White

Recessed luminaire with LED light source. Power supply not included. One driver is needed per each light source.

Main specifications

Mountings	Ceiling recessed
Environment	Indoor dry location

Electrical



Emergency	Without
Insulation class	III

Physical

Color	White
Weight (kg)	0.30

Note

Unique reference for Trim or No Trim recessed installation. 08.0550.00=includes white frame to complete Trim finishing. 08.0500.00=includes optional white and black frames to complete Trim finishing.




Johnny 120 Square 1L – Recessed Universal Frame



Continuous current power supply of 18W, 220/240V – 50/60Hz with 450 mA supply voltage Mains dimming, trailing edge
60.9268

Snoot shielding cone
08.0526.BW

Continuous current power supply 220/240V – 50/60Hz. Adjustable Current 300mA-13W / 350mA-15W / 400mA-18W / 450mA-20W / 500mA-22W / 550mA-24W / 600mA-27W / 650mA-29W / 700mA-31W / 750mA-32W / 800mA-33W / 850mA-35W / 900mA-38W / 950mA-40W / 1000/1050mA-42W
60.9162



Elliptical lens
08.8431.00

Continuous current power supply. 230/240V – 50/60Hz. Adjustable Current 350mA – 17W / 500mA – 24W / 700/ 750 mA – 32W switch by trailing and leading edge dimming, mains dimming or push dimming
60.8534

Flood lens
08.8432.00



Snoot shielding cone
08.0526.00



Snoot shielding cone
08.0526.40



Honeycomb
08.8428.00



Continuous current power supply of
13-20W, 110/240V – 50/60Hz with power
current selected through adjustable
300 mA – 15W / 350 mA – 18W /
400/450/500/550/600/
650/700/750/800/850/900 mA – 15W.
switch. 0/1-10V or push dimming
60.9188



Continuous current power supply of
10-20W, 110/240V – 50/60Hz with power
current selected through adjustable
250 mA – 10W / 350 mA – 15W / 400 mA
– 17W / 450 mA – 19W / 500/550/600/700
mA – 20W, Dali 1 switch.
60.8847