



### Junco 400 mm

08.8596.06A - Chrome

Luminaire that offers many possibilities. Can be individually focused and their recessed height is adjustable.

#### Main specifications

<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling recessed
<b>Power (W)</b>	2.2W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	2700K		
<b>CRI</b>	90		
<b>Net lumen (lm)</b>	130		

#### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Power LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Accent light
<b>Beam angle (°)</b>	15

#### Electrical


<b>Voltage (V)</b>	3.00
<b>Dimmable</b>	No
<b>Driver</b>	Remote excluded
<b>Driver type</b>	Non Dimmable, Dimmable Push, Dimmable 1-10V
<b>Emergency</b>	Without

#### Physical

<b>Color</b>	Chrome	<b>Rotation (°)</b>	360
<b>Orientation</b>	Adjustable	<b>Length (mm)</b>	400
<b>Recessed depth (mm)</b>	360		
<b>Weight (kg)</b>	0.19		
<b>Tilt (°)</b>	20		

#### Note

Soft Plate to be order separately.



## Junco 400 mm



---

Continuous current power supply of 17/24/32W, 220/240V – 50/60Hz with power current selected through adjustable 350 mA -17W / 500 mA – 24W / 700 mA – 32W switch  
60.8656



---

Not dimmable continuous current power supply of 17W, 700 mA – 110/240V – 50/60Hz  
60.8655



---

Continuous current power supply of 25W, 110/240V – 50/60Hz with power current selected through adjustable 350 mA-18W / 400 mA – 21W / 500mA – 25W /600mA – 30W /700/750/900 mA – 32W switch. 1-10V or push dimming, synchronisation cables not included.  
60.8533