









Junco 400 mm

08.8596.40A - White

Luminaire that offers many possibilities. Can be individually focused and their recessed height is adjustable.

Main specifications			
Lamp category Power (W) CCT (K) CRI Net lumen (lm)	LED 2.2W 2700K 90 130	Mountings Environment	Ceiling recessed Indoor dry location
Optical			
Lighting type LED type Light distribution Optical type Beam angle (°)	Direct Power LED Symmetric Accent light 15		
Electrical			
Voltage (V) Dimmable Driver	3.00 No Remote excluded		
Driver type Emergency	Non Dimmable, Dimmable Push, Dimmable 1-10V Without		
Physical			
Color Orientation Recessed depth (mm) Weight (kg) Tilt (°)	White Adjustable 360 0.19 20	Rotation (°) Length (mm)	360 400

Note

Soft Plate to be order separately.

Junco 400 mm







Continuous current power supply of 17/24/32W, 220/240V – 50/60Hz with power current selected through adjustable 350 mA -17W / 500 mA – 24W / 700 mA – 32W switch 60.8656

Not dimmable continuous current power supply of 17W, 700 mA – 110/240V – 50/60Hz 60.8655 Continuous current power supply of 25W, 110/240V – 50/60Hz with power current selected through adjustable 350 mA-18W / 400 mA – 21W / 500mA – 25W /600mA – 30W /700/750/900 mA – 32W switch. 1-10V or push dimming, synchronisation cables not included. 60.8533