

Kap 105 Square

■ 03.4572.74 - Black

Recessed 12V lamp luminaire. Remote transformer not included.


Recessed 12V lamp luminaire. Remote transformer not included.

Main specifications

Number of heads	1	Environment	Indoor dry location
Lamp category	LED		
Power (W)	50W Max		
Net lumen (lm)	315		
Mountings	Ceiling recessed		

Optical

Lighting type	Direct
Lamp type	QR-CBC 51
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	44
Beam angle C90-270 (°)	43



Beam Angle:	43°	
h(m)	E(lx)	D(m)
1	604	0.80
2	151	1.61
3	67	2.41
4	38	3.22
5	24	4.02

Luminous flux luminaire
995 lm (EXTREME CUT OFF)

Electrical


Frequency (Hz)	50/60	Driver type	Electronic 12V
Voltage (V)	12.00	Emergency	Without
Lamp holder	GX5.3	Insulation class	III
Dimmable	No		
Driver	Remote excluded		

Physical

Color	Black
Orientation	Fixed
Recessed depth (mm)	185
Weight (kg)	0.55

Note

Pre-installation frame. To be ordered separately. Not suitable for lens accessories.



Kap 105 Square



12V Electronic Transformer 20-70W for
LED Bulbs and Halogen Lamps
60.9398

12V electronic transformer. 220/240V,
50/60Hz. Adjustable by means of
"leading and trailing edge"
60.9424