













Recessed 12V lamp luminaire. Remote transformer not included.

Recessed 12V lamp luminaire. Remote transformer not included.


### Main specifications

Number of heads Lamp category LED MAX 50W Power (W) System power (W) 50 Net lumen (lm) 423

Mountings **Environment**  Ceiling recessed Indoor dry location

## Optical

Lighting type Direct QR-CBC 51 Lamp type Light distribution Symmetric Optical type Spot Beam angle (°) Beam angle C90-270 (°) 45



Luminous flux luminaire 995 lm (EXTREME CUT OFF)

Beam Angle:		45°
h(m)	E( <b>l</b> x)	D(m)
1	656	0.80
2	164	1.61
3	73	2.41
4	41	3.22
5	26	4.02

#### Electrical

Voltage (V) 12 Current (mA) -9 Lamp holder GX5.3 Dimmable No Driver Remote excluded Driver type Emergency Insulation class Electronic 12V Without

### **Physical**

Color White Orientation Fixed Recessed depth (mm) 185 Weight (kg) 0.55

#### Note

Pre-installation frame. To be ordered separately. Not suitable for lens accessories.

# Kap 105 Square





12V Electronic Transformer 20-70W for LED Bulbs and Halogen Lamps 60.9398 12V electronic transformer. 220/240V, 50/60Hz. Adjustable by means of "leading and trailing edge" 60.9424