

Kap 105 Square

03.4572.GL - Gold

Recessed 12V lamp luminaire. Remote transformer not included.


Recessed 12V lamp luminaire. Remote transformer not included.

Main specifications

Number of heads	1	Mountings	Ceiling recessed
Lamp category	LED	Environment	Indoor dry location
Power (W)	MAX 50W		
System power (W)	50		
Net lumen (lm)	420		

Optical

Lighting type	Direct
Lamp type	QR-CBC 51
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	46
Beam angle C90-270 (°)	46



Beam Angle: 46°

h(m)	E(lx)	D(m)
1	655	0.84
2	164	1.69
3	73	2.53
4	41	3.37
5	26	4.21

Luminous flux luminaire
995 lm (EXTREME CUT OFF)

Electrical

Voltage (V)	12	Driver type	Electronic 12V
Current (mA)	-9	Emergency	Without
Lamp holder	GX5.3	Insulation class	III
Dimmable	No		
Driver	Remote excluded		

Physical

Color	Gold
Orientation	Fixed
Recessed depth (mm)	185
Weight (kg)	0.55

Note

Pre-installation frame. To be ordered separately. Not suitable for lens accessories.

Kap 105 Square



12V electronic transformer. 220/240V,
50/60Hz. Adjustable by means of
"leading and trailing edge"
60.9424

12V Electronic Transformer 20-70W for
LED Bulbs and Halogen Lamps
60.9398