


Kap 105 Square 1-10V

03.4570.B1C1V - White

Recessed luminaire with LED light source. Remote electronic transformer 220/240V included.




Main specifications

| | | | |
|------------------------|-------|-----------------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 592 |
| Lamp category | LED | Mountings | Ceiling recessed |
| Power (W) | 17W | Environment | Indoor dry location |
| CCT (K) | 3000K | | |
| CRI | 98 | | |

Optical

| | |
|-------------------------------|--------------|
| Lighting type | Direct |
| LED type | Phosphor LED |
| Light distribution | Symmetric |
| Optical type | Flood |
| Beam angle (°) | 45 |
| Beam angle C90-270 (°) | 45 |
| Efficiency (lm/W) | 34 |



| | | | |
|--------------------|--------------|-------------|--|
| Beam Angle: | 45° | | |
| h(m) | E(lx) | D(m) | |
| 1 | 827 | 0.82 | |
| 2 | 207 | 1.64 | |
| 3 | 92 | 2.46 | |
| 4 | 52 | 3.28 | |
| 5 | 33 | 4.11 | |

Luminous flux luminaire
592 lm (EXTREME CUT OFF)

Electrical

| | | | |
|-----------------------|-----------------|-------------------------|---------|
| Frequency (Hz) | 50/60 | Emergency | Without |
| Voltage (V) | 18.40 | Insulation class | II |
| Dimmable | Yes | | |
| Driver | Remote included | | |
| Driver type | Dimmable 1-10V | | |

Physical

| | |
|--------------------|-------|
| Color | White |
| Orientation | Fixed |
| Weight (kg) | 0.84 |

Note

Pre-installation frame. To be ordered separately.



Kap 105 Square 1-10V



Installation frame No Trim
08.8479.00