


Kap 105 Square 1-10V

■ 03.4570.CUC1V - Copper

Recessed luminaire with LED light source. Remote electronic transformer 220/240V included.




Main specifications

Number of heads	1	Net lumen (lm)	585
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	17W	Environment	Indoor
CCT (K)	3000K		
CRI	98		

Optical

Lighting type	Direct
LED type	Phosphor LED
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	41
Beam angle C90-270 (°)	42



Beam Angle:	41°		
h(m)	E(lx)	D(m)	
1	1173	0.74	
2	293	1.48	
3	130	2.22	
4	73	2.96	
5	47	3.69	

Luminous flux luminaire
585 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	18.40	Insulation class	II
Dimmable	Yes		
Driver	Remote		
Driver type	Electronic dimmable 1-10V		

Physical

Color	Copper
Orientation	Fixed
Weight (kg)	0.84
Spot diameter (mm)	105

Certification / Marking



Note

Pre-installation frame. To be ordered separately.

Kap 105 Square 1-10V



Installation frame No Trim
08.8479.00