


Kap 105 Square 1-10V

■ 03.4582.BU.1V - Blue

Recessed luminaire with LED light source. Remote electronic transformer 220/240V included.




Main specifications

Number of heads	1	Net lumen (lm)	742
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	17W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	40
Beam angle C90-270 (°)	40
Efficiency (lm/W)	43



Beam Angle:	40°		
h(m)	E(lx)	D(m)	
1	1600	0.72	
2	400	1.44	
3	178	2.16	
4	100	2.88	
5	64	3.60	

Luminous flux luminaire
742 lm (EXTREME CUT OFF)

Electrical


Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	28.10	Insulation class	II
Dimmable	Yes		
Driver	Remote included		
Driver type	Dimmable 1-10V		

Physical

Color	Blue
Orientation	Fixed
Weight (kg)	0.84

Note

Pre-installation frame. To be ordered separately.



Kap 105 Square 1-10V



Installation frame No Trim
08.8479.00