



## Kap 105 Square 1-10V

03.4595.B1C1V - White

Recessed luminaire with LED light source. Remote electronic transformer 220/240V included.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	592
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling recessed
<b>Power (W)</b>	17W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	2700K		
<b>CRI</b>	98		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Phosphor LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Flood
<b>Beam angle (°)</b>	45
<b>Beam angle C90-270 (°)</b>	45



<b>Beam Angle:</b>	45°		
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>	
1	827	0.82	
2	207	1.64	
3	92	2.46	
4	52	3.28	
5	33	4.11	

Luminous flux luminaire  
592 lm (EXTREME CUT OFF)

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	18.40	<b>Insulation class</b>	II
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote		
<b>Driver type</b>	Electronic dimmable 1-10V		


### Physical

<b>Color</b>	White
<b>Orientation</b>	Fixed
<b>Weight (kg)</b>	0.84
<b>Spot diameter (mm)</b>	105

### Note

Pre-installation frame. To be ordered separately.

### Certification / Marking



## Kap 105 Square 1-10V



---

Installation frame No Trim  
08.8479.00