


## Kap 105 Square 1-10V

03.4595.CUC1V - Copper

Recessed luminaire with LED light source. Remote electronic transformer 220/240V included.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	585
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling recessed
<b>Power (W)</b>	17W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	2700K		
<b>CRI</b>	98		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Phosphor LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Flood
<b>Beam angle (°)</b>	41
<b>Beam angle C90-270 (°)</b>	42
<b>Efficiency (lm/W)</b>	34



<b>Beam Angle:</b>	41°		
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>	
1	1173	0.74	
2	293	1.48	
3	130	2.22	
4	73	2.96	
5	47	3.69	

Luminous flux luminaire  
585 lm (EXTREME CUT OFF)

### Electrical


<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	18.40	<b>Insulation class</b>	II
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote included		
<b>Driver type</b>	Dimmable 1-10V		

### Physical

<b>Color</b>	Copper
<b>Orientation</b>	Fixed
<b>Weight (kg)</b>	0.84

### Note

Pre-installation frame. To be ordered separately.



## Kap 105 Square 1-10V



---

Installation frame No Trim  
08.8479.00