

Kap 105 Square 1-10V

03.4595.GLC1V - Gold


Recessed luminaire with LED light source. Remote electronic transformer 220/240V included.

Main specifications

Number of heads	1	CRI	98
Lamp category	LED	Net lumen (lm)	581
Power (W)	17W	Mountings	Ceiling recessed
System power (W)	17	Environment	Indoor dry location
CCT (K)	2700K		

Optical

Lighting type	Direct
LED type	Phosphor LED
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	45
Beam angle C90-270 (°)	45
UGRL	13
Efficiency (lm/W)	34



Beam Angle: 45°

h(m)	E(lx)	D(m)
1	896	0.82
2	224	1.64
3	100	2.47
4	56	3.29
5	36	4.11

Luminous flux luminaire
581 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Driver type	Dimmable 1-10V
Voltage (V)	18	Emergency	Without
Current (mA)	700	Insulation class	II
Dimmable	Yes		
Driver	Remote included		

Physical

Color	Gold
Orientation	Fixed
Weight (kg)	0.84
Lifespan (L70 B10)	L80B50

Note

Pre-installation frame. To be ordered separately.

Kap 105 Square 1-10V



Installation frame No Trim
08.8479.00