


## Kap 105 Square Dali

03.4583.B1.DA - White

Recessed luminaire with LED light source. Remote electronic transformer 220/240V included.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	946
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling recessed
<b>Power (W)</b>	17W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	2700K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Flood
<b>Beam angle (°)</b>	40
<b>Beam angle C90-270 (°)</b>	40
<b>Efficiency (lm/W)</b>	55



Beam Angle: 40°		
h(m)	E(lx)	D(m)
1	1701	0.72
2	425	1.44
3	189	2.16
4	106	2.87
5	68	3.59

Luminous flux luminaire  
946 lm (EXTREME CUT OFF)

### Electrical


<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	28.10	<b>Insulation class</b>	II
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote included		
<b>Driver type</b>	Dimmable DALI		
	1		

### Physical

<b>Color</b>	White
<b>Orientation</b>	Fixed
<b>Weight (kg)</b>	0.84

### Note

Pre-installation frame. To be ordered separately.



## Kap 105 Square Dali



---

Installation frame No Trim  
08.8479.00