




Kap 80 Plus Square Adjustable Optic Medium

Update

■ 05.7416.BU - Blue

Recessed luminaire with LED light source. Power supply not included Diffusing lens included.




Main specifications

| | | | |
|------------------------|-------|-----------------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 748 |
| Lamp category | LED | Mountings | Ceiling recessed |
| Power (W) | 13.4W | Environment | Indoor dry location |
| CCT (K) | 3000K | | |
| CRI | 90 | | |

Optical

| | |
|-------------------------------|-----------|
| Lighting type | Direct |
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Medium |
| Beam angle (°) | 27 |
| Beam angle C90-270 (°) | 28 |
| Efficiency (lm/W) | 55 |



| | | | |
|--------------------|--------------|-------------|--|
| Beam Angle: | 27° | | |
| h(m) | E(lx) | D(m) | |
| 1 | 1970 | 0.47 | |
| 2 | 492 | 0.94 | |
| 3 | 219 | 1.41 | |
| 4 | 123 | 1.88 | |
| 5 | 79 | 2.36 | |

Luminous flux luminaire
748 lm (EXTREME CUT OFF)

Electrical

| | | | |
|---------------------|---|-------------------------|---------|
| Voltage (V) | 17,8 | Emergency | Without |
| Current (mA) | 700 | Insulation class | III |
| Dimmable | Yes | | |
| Driver | Remote excluded | | |
| Driver type | Non Dimmable, Dimmable DALI 2, Dimmable 0-10V, Dimmable Casambi, Dimmable 1-10V, Dimmable DALI 1, Mains Cut Dimming | | |

Physical

| | | | |
|----------------------------|------------|---------------------|-----|
| Color | Blue | Rotation (°) | 360 |
| Orientation | Adjustable | | |
| Recessed depth (mm) | 150 | | |
| Weight (kg) | 0,241 | | |
| Tilt (°) | 20 | | |

Kap 80 Plus Square Adjustable Optic Medium



Continuous current power supply, dimmable Casambi 220/240V-50/60Hz, 300mA-16W / 350mA-18,5W / 400mA-21,5W / 450mA-24W / 500mA-27W / 600mA-32W / 650mA-35W / 700mA-36W / 750/800/900/1000/1050mA – 38W
60.9207



Continuous current power supply, Mains dimming, leading & trailing edge 220/240V – 50/60Hz, 300mA-14W / 350mA-17W / 400mA-19W / 450/500/600/650/700/750/800/900mA – 20W
60.9467




Continuous current power supply of 12-20W, 110/240V – 50/60Hz with power current selected through adjustable 350mA – 17W / 400mA – 19W / 450 / 550 / 600 / 700mA – 20W regulable Dali 1 y Dali 2
60.9222



Non dimmable continuous current power supply. 15-30W, 220/240V -50/60Hz with power current selected through adjustable switch. 350mA – 15W / 400mA – 17W / 450mA – 19W / 500mA – 22W / 550mA – 24W / 600mA – 26W / 650mA – 28W / 700mA – 30W no regulable
60.9592



Continuous current power supply of 13-20W, 110/240V – 50/60Hz with power current selected through adjustable 300 mA – 15W / 350 mA – 18W / 400/450/500/550/600/ 650/700/750/800/850/900 mA – 15W. switch. 0/1-10V or push dimming
60.9188



Installation frame No Trim
08.9103.00



Continuous current power supply of
10-20W, 110/240V – 50/60Hz with power
current selected through adjustable
250 mA – 10W / 350 mA – 15W / 400 mA
– 17W / 450 mA – 19W / 500/550/600/700
mA – 20W, Dali 1 switch.
60.8847