



Kap 80 Plus Square Adjustable Optic Spot

■ 05.7463.BU - Blue

Recessed luminaire with LED light source. Power supply not included Diffusing lens included.




Main specifications

Number of heads	1	Net lumen (lm)	997
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	13.4W	Environment	Indoor
CCT (K)	2700K		
CRI	90		

Optical

LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	18
Beam angle C90-270 (°)	18




Beam Angle:	18°		
h(m)	E(lx)	D(m)	
1	3918	0.31	
2	979	0.62	
3	435	0.93	
4	245	1.24	
5	157	1.55	

Luminous flux luminaire
997 lm (EXTREME CUT OFF)

Electrical

Voltage (V)	17,8	Emergency	Without
Current (mA)	700	Insulation class	III
Dimmable	Yes		
Driver	Remote		
Driver type	Electronic, Electronic dimmable, Electronic dimmable 1-10V, Electronic dimmable DALI		


Certification / Marking



Physical

Color	Blue	Rotation (°)	360
Orientation	Adjustable	Spot diameter (mm)	80
Recessed depth (mm)	150	Length (mm)	74
Weight (kg)	0,241		
Tilt (°)	20		

Kap 80 Plus Square Adjustable Optic Spot



Installation frame No Trim
08.9103.00



Non dimmable continuous current
power supply. 15-30W, 220/240V
-50/60Hz with power current selected
through adjustable switch.
60.9592



Continuous current power supply of
13-20W, 110*/240V – 50/60Hz with
power current selected through
adjustable switch. Synchronisation
cables not included.
60.9188



Constant Current Power Supply for
LED. Dimmable DALI. 10-20W
60.8847



Continuous current power supply of
12-20W, 110*/240V – 50/60Hz with
power current selected through
adjustable. Regulable DALI 1 y DALI 2
60.9222



Continuous current power supply,
Mains dimming 220/240V – 50/60Hz, 12-
20W
60.9467



