


Kap 80 Plus Square Fixed Optic Spot

■ 05.7454.GL - Gold

Recessed luminaire with LED light source. Power supply not included Diffusing lens included.




Main specifications

Number of heads	1	Net lumen (lm)	1113
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	13.4W	Environment	Indoor
CCT (K)	3000K		
CRI	90		

Optical

LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	18
Beam angle C90-270 (°)	19




Beam Angle: 18°	h(m)	E(lx)	D(m)
	1	4231	0.31
	2	1058	0.63
	3	470	0.94
	4	264	1.26
	5	169	1.57

Luminous flux luminaire
1113 lm (EXTREME CUT OFF)

Electrical

Voltage (V)	17,8	Emergency	Without
Current (mA)	700	Insulation class	III
Dimmable	Yes		
Driver	Remote		
Driver type	Electronic, Electronic dimmable, Electronic dimmable 1- 10V, Electronic dimmable DALI		


Certification / Marking



Physical

Color	Gold	Length (mm)	74
Orientation	Fixed		
Recessed depth (mm)	150		
Weight (kg)	0,241		
Spot diameter (mm)	80		

Kap 80 Plus Square Fixed Optic Spot



Installation frame No Trim
08.9103.00



Non dimmable continuous current power supply. 15-30W, 220/240V -50/60Hz with power current selected through adjustable switch.
60.9592



Continuous current power supply of 13-20W, 110*/240V – 50/60Hz with power current selected through adjustable switch. Synchronisation cables not included.
60.9188



Constant Current Power Supply for LED. Dimmable DALI. 10-20W
60.8847



Continuous current power supply of 12-20W, 110*/240V – 50/60Hz with power current selected through adjustable. Regulable DALI 1 y DALI 2
60.9222



Continuous current power supply, Mains dimming 220/240V – 50/60Hz, 12-20W
60.9467



