


Kap 80 Square Adjustable Optic Flood - Dim-To-Warm

■ 03.4544.GL.LE - Gold

Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.

Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.




Main specifications

Number of heads	1	Net lumen (lm)	720
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	13W	Environment	Indoor dry location
CCT (K)	2850K-1800K		
CRI	95		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	53
Beam angle C90-270 (°)	51
Efficiency (lm/W)	55



Beam Angle:	53°
h(m)	E(lx) D(m)
1	1012 0.99
2	253 1.98
3	112 2.97
4	63 3.96
5	40 4.95

Luminous flux luminaire
720 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Driver type	Dimmable 1-10V
Voltage (V)	33.00	Emergency	Without
Current (mA)	300	Insulation class	II
Dimmable	Yes		
Driver	Remote included		

Physical


Color	Gold	Rotation (°)	360
Orientation	Adjustable		
Recessed depth (mm)	93		
Weight (kg)	0.24		
Tilt (°)	20		

Note

For 110V PSU versions, please consult with the front office. Diffusing lens included.



Kap 80 Square Adjustable Optic Flood - Dim-To-Warm



Installation frame No Trim
08.9103.00