



Kap 80 Square Adjustable Optic Medium - Dim-To-Warm

■ 03.4186.BU.LE - Blue

Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.

Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.




Main specifications

Number of heads	1	Net lumen (lm)	696
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	13W	Environment	Indoor dry location
CCT (K)	2850K-1800K		
CRI	95		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	27
Beam angle C90-270 (°)	27
Efficiency (lm/W)	53



Beam Angle: 27°

h(m) E(lx) D(m)

1 1786 0.47

2 447 0.95

3 198 1.42

4 112 1.89

5 71 2.37

Luminous flux luminaire
696 lm (EXTREME CUT OFF)

Electrical


Frequency (Hz)	50/60	Driver type	Dimmable 1-10V
Voltage (V)	33.00	Emergency	Without
Current (mA)	300	Insulation class	II
Dimmable	Yes		
Driver	Remote included		

Physical


Color	Blue	Rotation (°)	360
Orientation	Adjustable		
Recessed depth (mm)	93		
Weight (kg)	0.24		
Tilt (°)	20		

Note

For 110V PSU versions, please consult with the front office. Diffusing lens included.



Kap 80 Square Adjustable Optic Medium - Dim-To-Warm



Installation frame No Trim
08.9103.00