




03.4190.BU.LE - Blue

Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.

Recessed luminaire with LED light source. 220-240V & dimmable 1-10V power supply included.




Number of heads	1	CRI	95
Lamp category	LED	Net lumen (lm)	632
	40144		0 11

Ceiling recessed Power (W) 13W Mountings System power (W) 13 Environment Indoor dry location CCT (K) 2850K-1800K



Indirect, Direct LED array Asymmetric Wall Washer Down
28
27
20
48



1214 0.68 2 304 1.35 3 135 2.03 2.71 76 49 3.39

Beam Angle: h(m) = E(Ix)

28°

D(m)

Luminous flux luminaire 632 lm (EXTREME CUT OFF)





## Electrical

Frequency (Hz)	50/60	Driver type	Dimmable 1-10V
Voltage (V)	33	Emergency	Without
Current (mA)	300	Insulation class	II
Dimmable	Yes		

Remote included





## Physical

Driver

Color	Blue
Orientation	Fixed
Recessed depth (mm)	81
Weight (kg)	0.24
Lifespan (L70 B10)	L80B50

## Note

For 110V PSU versions, please consult with the front office. Diffusing lens included.

## Kap 80 Square Wall-Washer - Dim-To-Warm



Installation frame No Trim 08.9103.00