

Kap 80 Surface Round Mains Dimming Optic Flood

■ □ 03.5944.14 - Black/White

Luminaire for mounting on the ceiling with LED light source. Power source incorporated into luminaire body. Mains dimming 220/240V (Leading & Trailing Edge).

Luminaire for mounting on the ceiling with LED light source. Power source incorporated into luminaire body. Mains dimming 220/240V (Leading & Trailing Edge).




Main specifications

| | | | |
|------------------------|-------|-----------------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 715 |
| Lamp category | LED | Mountings | Ceiling surface |
| Power (W) | 9.2W | Environment | Indoor dry location |
| CCT (K) | 3000K | | |
| CRI | 90 | | |

Optical

| | |
|-------------------------------|-----------|
| Lighting type | Direct |
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Flood |
| Beam angle (°) | 50 |
| Beam angle C90-270 (°) | 50 |



| | | | |
|-------------|------|-------|------|
| Beam Angle: | 50° | | |
| | h(m) | E(lx) | D(m) |
| 1 | 1108 | 0.93 | |
| 2 | 277 | 1.86 | |
| 3 | 123 | 2.79 | |
| 4 | 69 | 3.72 | |
| 5 | 44 | 4.65 | |

Luminous flux luminaire
715 lm (EXTREME CUT OFF)

Electrical

| | | | |
|-----------------------|----------------------|-------------------------|---------|
| Frequency (Hz) | 50/60 | Emergency | Without |
| Voltage (V) | 18.20 | Insulation class | I |
| Dimmable | Yes | | |
| Driver | Integrated | | |
| Driver type | Mains Cut Dimming | | |

Physical

| | |
|--------------------|-------------|
| Color | Black/White |
| Orientation | Fixed |
| Weight (kg) | 0.45 |

Note

There may be a 10% variation in the minimum dimming point between different luminaires.

