


## Kap 80 Surface Round Mains Dimming Optic Flood

03.5945.14 - Black/Gold

Luminaire for mounting on the ceiling with LED light source. Power source incorporated into luminaire body. Mains dimming 220/240V (Leading & Trailing Edge).

Luminaire for mounting on the ceiling with LED light source. Power source incorporated into luminaire body. Mains dimming 220/240V (Leading & Trailing Edge).




### Main specifications

Number of heads	1	Net lumen (lm)	687
Lamp category	LED	Mountings	Ceiling surface
Power (W)	9.2W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

### Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	45
Beam angle C90-270 (°)	45



Luminous flux luminaire  
687 lm (EXTREME CUT OFF)

Beam Angle: 45°

h(m)	E(lx)	D(m)
1	1255	0.83
2	314	1.66
3	139	2.48
4	78	3.31
5	50	4.14

### Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	18.20	Insulation class	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Mains Cut		
	Dimming		

### Physical

Color	Black/Gold
Orientation	Fixed
Weight (kg)	0.45

### Note

There may be a 10% variation in the minimum dimming point between different luminaires.

