



## Kap 80 Surface Round Mains Dimming Optic Medium

 **03.5906.14 - Black/Copper**

Luminaire for mounting on the ceiling with LED light source. Power source incorporated into luminaire body. Mains dimming 220/240V (Leading & Trailing Edge).

Luminaire for mounting on the ceiling with LED light source. Power source incorporated into luminaire body. Mains dimming 220/240V (Leading & Trailing Edge).




### Main specifications

Number of heads	1	Net lumen (lm)	595
Lamp category	LED	Mountings	Ceiling surface
Power (W)	9.2W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

### Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	29
Beam angle C90-270 (°)	29



Luminous flux luminaire  
595 lm (EXTREME CUT OFF)

Beam Angle: 29°

	h(m)	E(lx)	D(m)
1	1764	0.51	
2	441	1.03	
3	196	1.54	
4	110	2.05	
5	71	2.57	

### Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	18.20	Insulation class	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Mains Cut		
	Dimming		

### Physical

Color	Black/Copper
Orientation	Fixed
Weight (kg)	0.45

### Note

There may be a 10% variation in the minimum dimming point between different luminaires.

