

Kap 80 Surface Round Mains Dimming Optic Medium

■ 03.5907.B1 - White/Black



Luminaire for mounting on the ceiling with LED light source. Power source incorporated into luminaire body. Mains dimming 220/240V (Leading & Trailing Edge).


Luminaire for mounting on the ceiling with LED light source. Power source incorporated into luminaire body. Mains dimming 220/240V (Leading & Trailing Edge).

Main specifications

| | | | |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 563 |
| Lamp category | LED | Mountings | Ceiling surface |
| Power (W) | 9.2W | Environment | Indoor dry location |
| CCT (K) | 3000K | | |
| CRI | 90 | | |

Optical

| | |
|------------------------|-----------|
| Lighting type | Direct |
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Medium |
| Beam angle (°) | 25 |
| Beam angle C90-270 (°) | 25 |



Beam Angle: 25°

| | h(m) | E(lx) | D(m) |
|---|------|-------|------|
| 1 | 1859 | 0.45 | |
| 2 | 465 | 0.89 | |
| 3 | 207 | 1.34 | |
| 4 | 116 | 1.79 | |
| 5 | 74 | 2.23 | |

Luminous flux luminaire
563 lm (EXTREME CUT OFF)

Electrical

| | | | |
|----------------|----------------------|------------------|---------|
| Frequency (Hz) | 50/60 | Emergency | Without |
| Voltage (V) | 18.20 | Insulation class | I |
| Dimmable | Yes | | |
| Driver | Integrated | | |
| Driver type | Mains Cut Dimming | | |

Physical

| | |
|-------------|-------------|
| Color | White/Black |
| Orientation | Fixed |
| Weight (kg) | 0.45 |

Note

There may be a 10% variation in the minimum dimming point between different luminaires.

