


Kap 80 Surface Round Mains Dimming Optic Spot

03.5922.18 - Deep Brown/Copper

Luminaire for mounting on the ceiling with LED light source. Power source incorporated into luminaire body. Mains dimming 220/240V (Leading & Trailing Edge).

Luminaire for mounting on the ceiling with LED light source. Power source incorporated into luminaire body. Mains dimming 220/240V (Leading & Trailing Edge).




Main specifications

| | | | |
|------------------------|-------|-----------------------|-----------------|
| Number of heads | 1 | Net lumen (lm) | 497 |
| Lamp category | LED | Mountings | Ceiling surface |
| Power (W) | 9.2W | Environment | Indoor |
| CCT (K) | 2700K | | |
| CRI | 90 | | |

Optical

| | |
|-------------------------------|-----------|
| Lighting type | Direct |
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Spot |
| Beam angle (°) | 22 |
| Beam angle C90-270 (°) | 22 |



| | | |
|------------------------|--------------|-------------|
| Beam Angle: 22° | | |
| h(m) | E(lx) | D(m) |
| 1 | 1977 | 0.40 |
| 2 | 494 | 0.79 |
| 3 | 220 | 1.19 |
| 4 | 124 | 1.58 |
| 5 | 79 | 1.98 |

Luminous flux luminaire
497 lm (EXTREME CUT OFF)

Electrical

| | | | |
|-----------------------|---------------------|-------------------------|---------|
| Frequency (Hz) | 50/60 | Emergency | Without |
| Voltage (V) | 18.20 | Insulation class | I |
| Dimmable | Yes | | |
| Driver | Integrated | | |
| Driver type | Electronic dimmable | | |

Physical

| | |
|--------------------|-------------------|
| Color | Deep Brown/Copper |
| Orientation | Fixed |
| Weight (kg) | 0.45 |

