

Kap 80 Surface Round Optic Flood Dali/Push Version

03.6044.B1.DA - White/White

Luminaire for mounting on the ceiling with LED light source. Power source incorporated into luminaire body.
Dali/Push dimming 220/240V.




Main specifications

Number of heads	1	Net lumen (lm)	715
Lamp category	LED	Mountings	Ceiling surface
Power (W)	9.2W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	50
Beam angle C90-270 (°)	50



Beam Angle: 50°

	h(m)	E(lx)	D(m)
--	------	-------	------

1	1108	0.93
---	------	------

2	277	1.86
---	-----	------

3	123	2.79
---	-----	------

4	69	3.72
---	----	------

5	44	4.65
---	----	------

Luminous flux luminaire
715 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	18.20	Insulation class	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmable Push, Dimmable DALI		
	1		

Physical

Color	White/White
Orientation	Fixed
Weight (kg)	0.45

