

## Kap 80 Surface Round Optic Flood Dali/Push Version

 **03.6046.18.DA - Deep Brown/Copper**

Luminaire for mounting on the ceiling with LED light source. Power source incorporated into luminaire body.  
Dali/Push dimming 220/240V.




### Main specifications

Number of heads	1	Net lumen (lm)	676
Lamp category	LED	Mountings	Ceiling surface
Power (W)	9.2W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

### Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	45
Beam angle C90-270 (°)	45



Beam Angle: 45°

	h(m)	E(lx)	D(m)
1	1165	0.83	
2	291	1.66	
3	129	2.49	
4	73	3.32	
5	47	4.14	

Luminous flux luminaire  
676 lm (EXTREME CUT OFF)

### Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	18.20	Insulation class	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmable Push, Dimmable DALI		
	1		

### Physical

Color	Deep Brown/Copper
Orientation	Fixed
Weight (kg)	0.45

