



## Kap 80 Surface Round Optic Medium

 **03.6001.18 - Deep Brown/Gold**

Luminaire for mounting on the ceiling with LED light source. Power source incorporated into luminaire body. Non dimmable 110/240V.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	594
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling surface
<b>Power (W)</b>	9.2W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	2700K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Medium
<b>Beam angle (°)</b>	26
<b>Beam angle C90-270 (°)</b>	26



Beam Angle: 26°

h(m)	E(lx)	D(m)
1	1926	0.46
2	481	0.92
3	214	1.38
4	120	1.84
5	77	2.30

Luminous flux luminaire  
594 lm (EXTREME CUT OFF)

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	18.20	<b>Insulation class</b>	I
<b>Dimmable</b>	No		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Electronic		

### Physical

<b>Color</b>	Deep Brown/Gold
<b>Orientation</b>	Fixed
<b>Weight (kg)</b>	0.45

### Certification / Marking

