

## Kap 80 Surface Round Optic Medium Dali/Push Version

■ □ 03.6000.18.DA - Deep Brown/White

Luminaire for mounting on the ceiling with LED light source. Power source incorporated into luminaire body. Dali/Push dimming 220/240V.




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	606
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling surface
<b>Power (W)</b>	9.2W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	2700K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Medium
<b>Beam angle (°)</b>	26
<b>Beam angle C90-270 (°)</b>	26



<b>Beam Angle:</b>	26°		
	<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>
1	1796	0.46	
2	449	0.92	
3	200	1.39	
4	112	1.85	
5	72	2.31	

Luminous flux luminaire  
606 lm (EXTREME CUT OFF)

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	18.20	<b>Insulation class</b>	I
<b>Dimmable</b>	Yes		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Dimmable Push, Dimmable DALI		
	1		

### Physical

<b>Color</b>	Deep Brown/White
<b>Orientation</b>	Fixed
<b>Weight (kg)</b>	0.45

