


Kap 80 Surface Round Optic Medium Dali/Push Version

03.6002.18.DA - Deep Brown/Copper

Luminaire for mounting on the ceiling with LED light source. Power source incorporated into luminaire body. Dali/Push dimming 220/240V.




Main specifications

Number of heads	1	Net lumen (lm)	572
Lamp category	LED	Mountings	Ceiling surface
Power (W)	9.2W	Environment	Indoor
CCT (K)	2700K		
CRI	90		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	29
Beam angle C90-270 (°)	29



Beam Angle:	29°		
h(m)	E(lx)	D(m)	
1	1695	0.51	
2	424	1.03	
3	188	1.54	
4	106	2.05	
5	68	2.57	

Luminous flux luminaire
572 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	18.20	Insulation class	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Electronic dimmable push, Electronic dimmable DALI		

Certification / Marking



Physical

Color	Deep Brown/Copper
Orientation	Fixed
Weight (kg)	0.45