

## Kap 80 Surface Round Optic Spot Dali/Push Version

■ 03.6020.14.DA - Black/White

Luminaire for mounting on the ceiling with LED light source. Power source incorporated into luminaire body.  
Dali/Push dimming 220/240V.




### Main specifications

Number of heads	1	Net lumen (lm)	710
Lamp category	LED	Mountings	Ceiling surface
Power (W)	9.2W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	90		

### Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	19
Beam angle C90-270 (°)	19



Beam Angle: 19°

h(m)	E(lx)	D(m)
------	-------	------

1	2684	0.34
---	------	------

2	671	0.68
---	-----	------

3	298	1.02
---	-----	------

4	168	1.36
---	-----	------

5	107	1.70
---	-----	------

Luminous flux luminaire  
710 lm (EXTREME CUT OFF)

### Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	18.20	Insulation class	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmable Push, Dimmable DALI		
	1		

### Physical

Color	Black/White
Orientation	Fixed
Weight (kg)	0.45

