

Kap 80 Surface Round Optic Spot Dali/Push Version

03.6021.B1.DA - White/Gold


Luminaire for mounting on the ceiling with LED light source. Power source incorporated into luminaire body.
Dali/Push dimming 220/240V.

**Main specifications**

Number of heads	1	Net lumen (lm)	684
Lamp category	LED	Mountings	Ceiling surface
Power (W)	9.2W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	90		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	19
Beam angle C90-270 (°)	19



Beam Angle: 19°

h(m)	E(lx)	D(m)
------	-------	------

1	2879	0.33
---	------	------

2	720	0.67
---	-----	------

3	320	1.00
---	-----	------

4	180	1.33
---	-----	------

5	115	1.66
---	-----	------

Luminous flux luminaire
684 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	18.20	Insulation class	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Dimmable Push, Dimmable DALI		
	1		

Physical

Color	White/Gold
Orientation	Fixed
Weight (kg)	0.45

