


Kap 80 Surface Square Mains Dimming Optic Flood

03.5950.18 - Deep Brown/White

Luminaire for mounting on the ceiling with LED light source. Power source incorporated into luminaire body. Mains dimming 220/240V (Leading & Trailing Edge).

Luminaire for mounting on the ceiling with LED light source. Power source incorporated into luminaire body. Mains dimming 220/240V (Leading & Trailing Edge).




Main specifications

Number of heads	1	Net lumen (lm)	723
Lamp category	LED	Mountings	Ceiling surface
Power (W)	9.2W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	90		

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	55
Beam angle C90-270 (°)	56



Beam Angle: 55°

h(m)	E(lx)	D(m)
1	921	1.03
2	230	2.07
3	102	3.10
4	58	4.14
5	37	5.17

Luminous flux luminaire
723 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	18.20	Insulation class	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Mains Cut Dimming		

Physical

Color	Deep Brown/White
Orientation	Fixed
Weight (kg)	0.45

Note

There may be a 10% variation in the minimum dimming point between different luminaires.

