

## Kap 80 Surface Square Mains Dimming Optic Flood

03.5951.18 - Deep Brown/Gold

Luminaire for mounting on the ceiling with LED light source. Power source incorporated into luminaire body. Mains dimming 220/240V (Leading & Trailing Edge).

Luminaire for mounting on the ceiling with LED light source. Power source incorporated into luminaire body. Mains dimming 220/240V (Leading & Trailing Edge).




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	704
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling surface
<b>Power (W)</b>	9.2W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	2700K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Flood
<b>Beam angle (°)</b>	53
<b>Beam angle C90-270 (°)</b>	54



Beam Angle: 53°		
h(m)	E(lx)	D(m)
1	990	1.00
2	248	2.00
3	110	3.00
4	62	4.00
5	40	5.01

Luminous flux luminaire  
704 lm (EXTREME CUT OFF)

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	18.20	<b>Insulation class</b>	I
<b>Dimmable</b>	Yes		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Mains Cut Dimming		

### Physical

<b>Color</b>	Deep Brown/Gold
<b>Orientation</b>	Fixed
<b>Weight (kg)</b>	0.45

### Note

There may be a 10% variation in the minimum dimming point between different luminaires.

