


Kap 80 Surface Square Mains Dimming Optic Flood

03.5951.B1 - White/Gold

Luminaire for mounting on the ceiling with LED light source. Power source incorporated into luminaire body. Mains dimming 220/240V (Leading & Trailing Edge).

Luminaire for mounting on the ceiling with LED light source. Power source incorporated into luminaire body. Mains dimming 220/240V (Leading & Trailing Edge).




Main specifications

| | | | |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 704 |
| Lamp category | LED | Mountings | Ceiling surface |
| Power (W) | 9.2W | Environment | Indoor dry location |
| CCT (K) | 2700K | | |
| CRI | 90 | | |

Optical

| | |
|------------------------|-----------|
| Lighting type | Direct |
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Flood |
| Beam angle (°) | 53 |
| Beam angle C90-270 (°) | 54 |



Luminous flux luminaire
704 lm (EXTREME CUT OFF)

Beam Angle: 53°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1 | 990 | 1.00 |
| 2 | 248 | 2.00 |
| 3 | 110 | 3.00 |
| 4 | 62 | 4.00 |
| 5 | 40 | 5.01 |

Electrical

| | | | |
|----------------|------------|------------------|---------|
| Frequency (Hz) | 50/60 | Emergency | Without |
| Voltage (V) | 18.20 | Insulation class | I |
| Dimmable | Yes | | |
| Driver | Integrated | | |
| Driver type | Mains Cut | | |
| | Dimming | | |

Physical

| | |
|-------------|------------|
| Color | White/Gold |
| Orientation | Fixed |
| Weight (kg) | 0.45 |

Note

There may be a 10% variation in the minimum dimming point between different luminaires.

