

Kap 80 Surface Square Mains Dimming Optic Medium

■ 03.5914.18 - Deep Brown/White

Luminaire for mounting on the ceiling with LED light source. Power source incorporated into luminaire body. Mains dimming 220/240V (Leading & Trailing Edge).

Luminaire for mounting on the ceiling with LED light source. Power source incorporated into luminaire body. Mains dimming 220/240V (Leading & Trailing Edge).




Main specifications

| | | | |
|------------------------|-------|-----------------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 640 |
| Lamp category | LED | Mountings | Ceiling surface |
| Power (W) | 9.2W | Environment | Indoor dry location |
| CCT (K) | 3000K | | |
| CRI | 90 | | |

Optical

| | |
|-------------------------------|-----------|
| Lighting type | Direct |
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Medium |
| Beam angle (°) | 25 |
| Beam angle C90-270 (°) | 27 |



| Beam Angle: 25° | | |
|-----------------|-------|------|
| h(m) | E(lx) | D(m) |
| 1 | 1670 | 0.45 |
| 2 | 418 | 0.90 |
| 3 | 186 | 1.34 |
| 4 | 104 | 1.79 |
| 5 | 67 | 2.24 |

Luminous flux luminaire
640 lm (EXTREME CUT OFF)

Electrical

| | | | |
|-----------------------|----------------------|-------------------------|---------|
| Frequency (Hz) | 50/60 | Emergency | Without |
| Voltage (V) | 18.20 | Insulation class | I |
| Dimmable | Yes | | |
| Driver | Integrated | | |
| Driver type | Mains Cut Dimming | | |

Physical

| | |
|--------------------|---------------------|
| Color | Deep Brown/White |
| Orientation | Fixed |
| Weight (kg) | 0.45 |

Note

There may be a 10% variation in the minimum dimming point between different luminaires.

