



## Kap 80 Surface Square Mains Dimming Optic Medium

■ ■ 03.5915.14 - Black/Gold

Luminaire for mounting on the ceiling with LED light source. Power source incorporated into luminaire body. Mains dimming 220/240V (Leading & Trailing Edge).

Luminaire for mounting on the ceiling with LED light source. Power source incorporated into luminaire body. Mains dimming 220/240V (Leading & Trailing Edge).




### Main specifications

Number of heads	1	Net lumen (lm)	624
Lamp category	LED	Mountings	Ceiling surface
Power (W)	9.2W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

### Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	25
Beam angle C90-270 (°)	27



Beam Angle: 25°

h(m)	E(lx)	D(m)
1	1739	0.45
2	435	0.90
3	193	1.34
4	109	1.79
5	70	2.24

Luminous flux luminaire  
624 lm (EXTREME CUT OFF)

### Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	18.20	Insulation class	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Mains Cut Dimming		

### Physical

Color	Black/Gold
Orientation	Fixed
Weight (kg)	0.45

### Note

There may be a 10% variation in the minimum dimming point between different luminaires.

