


## Kap 80 Surface Square Mains Dimming Optic Spot

03.5931.18 - Deep Brown/Gold

Luminaire for mounting on the ceiling with LED light source. Power source incorporated into luminaire body. Mains dimming 220/240V (Leading & Trailing Edge).

Luminaire for mounting on the ceiling with LED light source. Power source incorporated into luminaire body. Mains dimming 220/240V (Leading & Trailing Edge).




### Main specifications

Number of heads	1	Net lumen (lm)	732
Lamp category	LED	Mountings	Ceiling surface
Power (W)	9.2W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	90		

### Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	18
Beam angle C90-270 (°)	19



Beam Angle: 18°

	h(m)	E(lx)	D(m)
1	2785	0.31	
2	696	0.63	
3	309	0.94	
4	174	1.26	
5	111	1.57	

Luminous flux luminaire  
732 lm (EXTREME CUT OFF)

### Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	18.20	Insulation class	I
Dimmable	Yes		
Driver	Integrated		
Driver type	Mains Cut Dimming		

### Physical

Color	Deep Brown/Gold
Orientation	Fixed
Weight (kg)	0.45

### Note

There may be a 10% variation in the minimum dimming point between different luminaires.

